

FICHA TÉCNICA/ DATA SHEET

TORNO HASS SL-30-THE

Marca: HASS

Modelo: SL-30-THE

Año: 2006

Referencia: CRN-002

Control: HASS



CAPACIDAD / CAPACITY

Diámetro sobre bancada/ **760 mm**

Diameter over bed

Diámetro sobre carro/ **368 mm**

Diameter on trolley

Diámetro sobre plato/ **210 mm**

Diameter over plate

Distancia entre centros/ **991 mm**

Distance between centres

Diámetro máximo pieza/ **432 mm**

Maximum workpiece diameter

GENERALES / GENERAL

Revoluciones/ **3400 rpm**

Revolutions

Par motor/ **407 Nm a 700 rpm**

Torque

Potencia máxima / **22 kw**

Maximum power

Nariz husillo / **A2-6**

Spindle nose

Agujero cabezal / **89 mm**

Head hole

Longitud máxima pieza /
Maximum piece length **864 mm**

Diámetro barra /
Bar diameter **76 mm**

RECORRIDOS / TRAVELS

Recorrido eje X /
X axis **287 mm**

Nº de herramientas /
No. of tools **12**

Recorrido eje Z /
Z axis **864 mm**

Tamaño herramienta /
Tool size **25x25 mm**

AVANCES / FEEDRATES

Avance rápido /
Rapid traverse **18 m/min**

Tiempo hta-hta /
Time **1 s**

Peso /
Weight **7258 kg**

IMÁGENES / PICTURES





HAAS MODEL **SL-30THE**
HAAS AUTOMATION, INC, OXNARD, CA. 93030
SERIAL NUMBER **3074967** CE
DATE OF MFG **09/96**
VOLTAGE 360/480
PHASE 3
HERTZ 50/60
FULL LOAD 40 AMPS
LARGEST LOAD 70 AMPS
SHORT CIRCUIT
INTERRUPTING CAPACITY - 10,000 AMPS
WIRING DIAGRAM **95** **8710**
NEMA TYPE 1 ENCLOSURE-FOR INDOOR USE ONLY.
OVER CURRENT PROTECTION PROVIDED
AT MACHINE SUPPLY TERMINALS.
WARNING
LETHAL VOLTAGES INSIDE CABINET!
DISCONNECT FROM POWER SOURCE
BEFORE OPENING CABINET!
TRAINED SERVICE PERSONNEL ONLY!
MADE IN U.S.A.
P/N 29-7900E REV. G