

FICHA TÉCNICA/ DATA SHEET

RECTIFICADORA DANOBAT RT 1200

Marca: DANOBAT

Modelo: RT-1200

Año: 2003

Referencia: ORL-1896

Control: FAGOR 102S



GENERAL/ GENERAL

Máx. longitud rectificable /
Max. grinding length **1200 mm**

Máx. anchura rectificable /
Max. grinding width **750 mm**

Máx. altura rectificable /
Max. grinding height **450 mm**

MESA / TABLE

Zona de apoyo de la
mesa / **1200x600 mm**
Table support area

Velocidad regulable /
Regulable speed range **1-40 m/min**

Peso máx. sobre la mesa/
Maximum weight on table **1250 kg**

CABEZAL / WHEELHEAD

Dimensiones máx. de la muela / **400x100x127 mm**

Maximum wheel dimensions

Velocidad muela / **1500 min⁻¹**

Wheel speed

Velocidad periférica de la muela/ **30 m/s**

Grinding wheel peripheral speed

MOTOR/ MOTOR

Cabezal / **11 KW**

Wheelhead

RECORRIDO VERTICAL/ VERTICAL TRAVEL

Velocidad programable/ **1-2000 mm/min**

Programmable speed

Incremento mínimo programable/ **0,001 mm**

Minimum programmable increment

RECORRIDO TRANSVERSAL / CROSS TRAVEL

Velocidad programable / **1-8000 mm/min**

Programmable speed

Incremento mínimo programable / **0,001 mm**

Minimum programmable increment

Velocidades/ **De 10 a 250 min⁻¹**

Speeds

VARIOS/ MISCELLANEOUS

Peso neto aproximado / **8300 kg**

Aproximate net weight

IMÁGENES / PICTURES

