

FICHA TÉCNICA/ DATA SHEET

TORNO CONVENCIONAL TRAVIS T-2260

Marca: TRAVIS

Modelo: T-2260

Año: 2017

Referencia: ORAL-0412



CAPACIDAD / CAPACITY

Volteo sobre bancada/ <i>Swing over bed</i>	560 mm	Altura de puntos/ <i>Center height</i>	280 mm
Volteo sobre carro transversal/ <i>Swing over cross slide</i>	340 mm	Distancia entre centros / <i>Distance between centers</i>	1500 mm
Volteo sobre escote/ <i>Swing over gap</i>	788 mm	Ancho de bancada/ <i>Bed width</i>	350 mm

HUSILLO / SPINDLE

Nariz de husillo/
Spindle nose **ASA D1-8**

Diámetro agujero de husillo/
Spindle bore diameter **85 mm**

Cono del agujero del husillo/
Spindle bore taper **MT 7**

Velocidades del husillo/
Spindle speeds **15 ~ 1500 rpm**

CONTRAPUNTO / TAILSTOCK

Cono de la manga /
Tailstock sleeve taper **MT5**

Carrera de la manga/
Tailstock sleeve travel **165 mm**

Diámetro de la manga /
Tailstock sleeve diameter **75 mm**

Carrera del carro transversal /
Cross slide travel **300 mm**

**Carrera del carro porta
herramientas /**
Tool holder slide travel **200 mm**

AVANCES / FEEDS

**Avances
longitudinales/**
Longitudinal feeds **0.05 ~ 0.82 mm**

**Avances
transversales/**
Cross feeds **0.02 ~ 0.4 mm**

MOTOR/ MOTOR

Motor principal /
Tailstock sleeve diameter **7,5 hp**

**Motor de la bomba
refrigerante /**
Tailstock sleeve internal taper **1/8 hp**

ROSCADOS/ THREADING

Roscas hilos por pulgadas/

Threads per inch **2 ~ 56 TPI**

Roscas métricas/

Metric threads **P0.5 ~ P14**

Diámetro del tornillo/

Leadscrew diameter **38 mm**

Paso del tornillo/

Leadscrew pitch **4 TPI o 6 mm/paso**

GENERAL/GENERAL

Dimensiones de la máquina/

Machine dimensions

2780*990*1250 mm

Peso neto/

Net weight

2200 kg

IMÁGENES / PICTURES

